

MWP04 Mini Wall Pack

10W/15W/20W | 3CCT | 120-347V

The successor to our MWP03 Mini Wall Packs!
Ideal for security lighting, commercial entrances,
stairways, perimeter areas, and more

Wet Location Rated
IP65

Colour Selectable
3000K / 4000K / 5000K

Low Glare, Frosted
Polycarbonate Lens

Built-In Photocell

120-347V
Universal Driver
0-10V dimming



Bronze Powder
Coat Finish
Also Available In Black



Power Selectable
10W / 15W / 20W



TECHNICAL DATA



LIGHT SPECIFICATIONS


Efficacy	125.27 lm/W
CCT	3000K/4000K/5000K
CRI	82
Beam Angle	100°
Dimmable	0-10V
L70 Life	>54,000 hrs
Warranty	10-year
Factory Settings	20W 4000K

LUMEN OUTPUT			
	3000K	4000K	5000K
10W	1322 lm	1394 lm	1437 lm
15W	1898 lm	2023 lm	2058 lm
20W	2557 lm	2729 lm	2749 lm

APPROVALS & LISTINGS

cUL	E482965
DLC Premium	S-0P4MJU

DIMENSIONAL DRAWINGS (IN)



ELECTRICAL

Wattage	10W/15W/20W
Voltage	120-347V
Current	0.25A
Surge Protection	2.5kV
Auxiliary Output	N/A
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C

CONSTRUCTION

Cord Whip	11.8"
Housing	Die-Cast Aluminum
Lens	Polycarbonate
Finish	Powder Coated
Finish Colour	Bronze
IP Rating	IP65

DIMENSIONS AND WEIGHTS

Fixture Weight	1.54 lbs
Fixture Dimensions	8.2 x 2.8 x 5 in
Carton Qty	1
Carton Weight	1.7 lbs
Carton Dimensions	8.6 x 3.2 x 5.3 in
Master Carton Qty	10
Master Carton Weight	19.86 lbs
Master Carton Dimensions	16.4 x 11.2 x 9.4 in